



# Air Max® Moisture Absorber

Effective TAB+ refills based on the most advanced technology in the field of moisture absorption.



**Fights Stains/residue:** Spilled fluid can cause surface marks. These spots continue to attract moisture. Remove stains with an abundance of water. Stains in textiles (floor coverings, lining) can be removed with sodium sulphate. Make a 5% solution with water (50 g/l) and spread it on the stain. Let it soak for approx. 30 minutes. Next, dry the stain by using a hairdryer or electric heater. Remove the remaining powder with a vacuum cleaner. Repeat the process if necessary. Rinse wash basin or sink with an abundance amount of water.

**Advice:** Always position the Air Max® Moisture Absorber Ambiance on a flat and stable surface.

## Technical specifications

**Chemical base:** Calcium chloride

**Colour:** White

## Storage conditions

At least 24 months after date of manufacture. Store in well-sealed packaging in a cool, dry and frost free place.

## Product description

Fights moisture throughout your living spaces.  
Effective TAB+ refills based on the most advanced technology in the field of moisture absorption.

## Field of application

Fights moisture throughout your living spaces.  
Suitable for use in the living room, bedroom, bathroom, toilet, etc.

## Properties

- Fits all Air Max® Moisture Absorber 450 g and 500 g devices.
- Powerful effect
  - Optimum moisture absorption
  - Clean, safe and hygienic
  - Available in neutral or with a subtle fragrance.

## Application

**Coverage:** 500 g works for approximately 3 months in a room up to approximately 50 m<sup>3</sup> and absorbs approximately 0.6 litres of water, depending on the temperature, humidity and size of the room.

## Directions for use:

1. Cut open the package containing the tab.
2. Lift the cap off the device and insert the tab without the packaging into the special holder.
3. Replace the cap on the device.
4. When the tab has dissolved completely, the device can easily be emptied.

Distributed by



Bay 2, Building 62 Third Avenue, Pensnett Trading Estate, Kingswinford, West Midlands, DY6 7XT  
TEL: 01384294753 FAX:01384297908 Email: [sales@cyanotec.com](mailto:sales@cyanotec.com)

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.