

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Lockfast MXP5 - COMPONENT A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Cyanotec Ltd

Bay 2 Building 62, Third Avenue,
Pensnett Trading Estate,
Kingswinford,
West Midlands DY6 7XT United Kingdom

Tel: +44 (0)1384 294753
Email: sales@cyanotec.com

1.4. Emergency telephone number

Emergency number : +44 (0) 1384 294753 (Monday - Thursday 9:00 to 17:00)

IN CASE OF TOXIC OR TRANSPORT EMERGENCY:
National Chemical Emergency Centre: Telephone 01865 407333

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Flam. Liq. 2: H225; Skin Corr. 1A: H314; Skin Sens. 1: H317;
STOT SE 3: H335

Most important adverse effects: Highly flammable liquid and vapour. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

UFI: W3D0-8005-7007-PEWD

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 2

Hazard statements: H225: Highly flammable liquid and vapour.
H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.
H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame
GHS05: Corrosion
GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241: Use explosion-proof equipment.
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P362+P364: Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

METHYL METHACRYLATE - REACH registered number(s): 01-2119452498-28-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
201-297-1	80-62-6	-	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	50-70%

2-METHYLPROPENOIC ACID - REACH registered number(s): 01-2119463884-26-XXXX

201-204-4	79-41-4	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1A: H314	1-10%
-----------	---------	---	--	-------

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 3

CUMENE HYDROPEROXIDE - REACH registered number(s): 01-2119475796-19-XXXX

201-254-7	80-15-9	-	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	---	-------

TOPANOL O - REACH registered number(s): 01-2119565113-46-XXXX

-	128-37-0	-	Aquatic Chronic 1: H410	0.1-1%
---	----------	---	-------------------------	--------

Non-classified ingredients:

IMPACT MODIFIER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
NA	NA	-	-	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact:** Corneal burns may occur. May cause permanent damage.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 4

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

METHYL METHACRYLATE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	50 ppm	100 ppm	-	-

2-METHYLPROPENOIC ACID

UK	72 mg/m ³	143 mg/m ³	-	-
----	----------------------	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Off-white

Odour: Characteristic odour

Viscosity: Highly viscous

Flash point°C: 11

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 6

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

METHYL METHACRYLATE

IPR	RAT	LD50	1328	mg/kg
ORL	MUS	LD50	3625	mg/kg
ORL	RAT	LD50	7872	mg/kg

2-METHYLPROPENOIC ACID

ORL	MUS	LD50	1250	mg/kg
ORL	RAT	LD50	1600	mg/kg

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 7

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT A

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H242: Heating may cause a fire.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Lockfast MXP5 - COMPONENT B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Cyanotec Ltd

Bay 2 Building 62, Third Avenue,
Pensnett Trading Estate,
Kingswinford,
West Midlands DY6 7XT United Kingdom

Tel: +44 (0)1384 294753
Email: sales@cyanotec.com

1.4. Emergency telephone number

Emergency number : +44 (0) 1384 294753 (Monday - Thursday 9:00 to 17:00)

IN CASE OF TOXIC OR TRANSPORT EMERGENCY:
National Chemical Emergency Centre: Telephone 01865 407333

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317;
STOT SE 3: H335

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

UFI: X6D0-R0PJ-H00Q-ASGF

Hazard statements: H225: Highly flammable liquid and vapour.

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 2

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P240: Ground and bond container and receiving equipment.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

P403+P235: Store in a well-ventilated place. Keep cool.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P273: Avoid release to the environment.

P370+P378: In case of fire: Use media other than water to extinguish.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P272: Contaminated work clothing should not be allowed out of the workplace.

P321: Specific treatment (see supplemental first aid instruction on this label)

P312: Call a POISON CENTRE or doctor if you feel unwell.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264: Wash hands, forearms and face thoroughly after handling.

P233: Keep container tightly closed.

P243: Take action to prevent static discharges.

P241: Use explosion-proof equipment.

P242: Use non-sparking tools.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 3

Hazardous ingredients:

METHYL METHACRYLATE - REACH registered number(s): 01-2119452498-28-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
201-297-1	80-62-6	-	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	70-90%

ADHESIVE ACTIVATOR - REACH registered number(s): REACH registration exemption - < 1 tonne

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	34562-31-7	-	Aquatic Chronic 4: H413; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H302+H312	1-10%

TOPANOL O - REACH registered number(s): 01-2119565113-46-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	128-37-0	-	Aquatic Chronic 1: H410	0.1-1%

Non-classified ingredients:

IMPACT MODIFIER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
NA	NA	-	-	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

METHYL METHACRYLATE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	50 ppm	100 ppm	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Green

Odour: Characteristic odour

Viscosity: Highly viscous

Flash point°C: 11

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 6

Hazardous ingredients:

METHYL METHACRYLATE

IPR	RAT	LD50	1328	mg/kg
ORL	MUS	LD50	3625	mg/kg
ORL	RAT	LD50	7872	mg/kg

ADHESIVE ACTIVATOR

DERMAL	RBT	LD50	>1000	mg/kg
ORAL	RAT	LD50	>500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 7

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H302+H312: Harmful if swallowed or in contact with skin

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

Lockfast MXP5 - COMPONENT B

Page: 8

H335: May cause respiratory irritation.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.